

COMPANY INFORMATION

COMPANY NAME: ORTHO SPECIALTIES
COMPANY ADDRESS: 3820 OHIO AVE - SUITE 15
 ST. CHARLES, IL 60174
COMPANY PHONE: 630-443-0225
COMPANY FAX: 630-443-0224
COMPANY WEB ADDRESS: www.orthospecialties.com

STAINLESS STEEL – TYPE 302	
DOCUMENT NUMBER:	SDS18
REVISION DATE:	09/26/2014
REVISION:	REV. E
NUMBER OF PAGES:	5

1.) PRODUCT IDENTIFICATION

1.1 Product Identifier:

Rotation Springs

Trade Names or Synonyms: 302 Stainless Steel ASTM A 493 - 95 (2004)

2.) INGREDIENTS HAZARDOUS

This section covers materials that may be present in the steel article purchased. Dependent on the customers' end-use, such as welding or grinding the metal, fumes, gases, and particulate may be generated; see section 3 for possible contaminant exposure scenarios.

Component		CAS#	wt %	PEL*	TLV*
Iron (Iron Oxide)	(Fe)	7439-89-6	<99.0	10 (iron oxide)	5(welding fume)
Chromium ³ [metal]	(Cr)	7440-47-3	<35.0	1	0.5
Nickel [metal]	(Ni)	7440-02-0	<35.0	1	0.5
Manganese	(Mn)	7439-96-5	<10.0	5C	0.2
Molybdenum	(Mo)	7439-98-7	<10.0	15	10 (TLV for insoluble compounds)
Tungston		7440-33-7	<6.5	NL	5 (TLV for insoluble compounds)
Cobalt	(Co)	7440-48-4	<4.5	0.1	0.02
Copper	(Cu)	7440-50-8	<4.5	1(Dusts/ mists) 0.1 (fumes)	1 (Dusts/ mists) 0.05 (fumes)
Vanadium	(V)	7440-62-2	<4.5	0.5C	0.05C (PEL/TLV for respirable Vanadium Pentoxide)
Silicon	(Si)	7440-21-3	<2.5	15(T) 5(R)	10
Titanium	(Ti)	7440-32-6	<2.5	15	10 (PEL/TLV for Titanium Dioxide)
Aluminum	(Al)	7429-90-5	<2.0	15(T) 5(R)	10 5 (TLV as Aluminum in welding fume)
Columbium	(Cb)	7440-03-1	<1.1	NL	NL
Sulfur	(S)	7704-34-9	<0.45	13	5.2 (PEL/TLV for sulfur dioxide)
Phosphorus	(P)		<0.45	<0.1	0.1
Tantalum	(Ta)	7440-25-7	0 - 1	None	5

*PEL - Permissible Exposure Limit - (mg/m3) - OSHA (29CFR1910)

*TLV - Threshold Limit Value - (mg/m3) - ACGIH

*C - Denotes Ceiling Level

COMPANY INFORMATION

COMPANY NAME: ORTHO SPECIALTIES
COMPANY ADDRESS: 3820 OHIO AVE - SUITE 15
 ST. CHARLES, IL 60174
COMPANY PHONE: 630-443-0225
COMPANY FAX: 630-443-0224
COMPANY WEB ADDRESS: www.orthospecialties.com

STAINLESS STEEL – TYPE 302	
DOCUMENT NUMBER:	SDS18
REVISION DATE:	09/26/2014
REVISION:	REV. E
NUMBER OF PAGES:	5

3.) HAZARDOUS IDENTIFICATION

HEALTH HAZARD OVERVIEW

Specialty steel alloys are generally not considered hazardous in the form shipped (solid bar, wire, strip, or billets). However, if your process involves grinding, melting, cutting or any other process that causes release of dust, or fume, hazardous levels of dust or fumes of the constituents of these alloys could be generated. The following is a list of potential health effects for the hazardous elements that may be contained in any on the alloys. Please refer to the hazardous ingredients preceding for a list of those specific elements contained in the particular alloy. It is the users responsibility to assess potential exposures based on their processing of the product. Additionally, protective coatings may have been applied to the steel at the request of the customer. The coating Would represent less than 0.5% of the total material present. Material safety data sheets are available for these products at your request.

GENERAL:

Welding Fume, fumes freshly generated by welding of zinc, magnesium and copper, are known to cause metal fume fever. Inhalation of aluminum, iron, nickel, manganese, selenium and tin have also been reported to cause metal fume fever. Symptoms are flu-like including: shortness of breath, coughing, muscle pain, fever and chills. Generally, symptoms resolve with rest in a few days.

EXPOSURE ROUTES:

Inhalation: Primary route of exposure, steel dusts and fume may cause irritation to the respiratory tract. Chronic Exposure may aggravate pre-existing conditions.

Skin & Eye Contact: May cause irritation or skin sensitivity.

Ingestion: Certain constituents may be harmful if swallowed.

SPECIFIC HEALTH EFFECTS:

ALUMINUM: Metal dust and oxide is generally considered a nuisance particulate. May irritate eyes and mucous membranes. Excessive concentrations have been known to cause fibrosis.

BORON OXIDE: An eye and respiratory irritant, may cause: eye irritation, dryness of mouth, nose and throat or a productive cough.

CHROMIUM: The toxicity of chromium is dependent on its oxidation rate. Chromium metal is relatively non-toxic. If metal is heated to high temperatures, as in welding, fumes produced may be toxic to the lungs. Under high temperatures, hexavalent chromium may be produced, if in the insoluble form it is designated confirmed human carcinogen. Other health effects include nasal irritation and possible kidney and liver damage. Chromite dust may also cause skin ulceration, dermatitis, and allergic skin reactions.

COBALT: May cause interstitial fibrosis, pneumonitis and sensitization of the respiratory tract and skin. Cobalt liberation during tungsten carbide machining is also associated with the development of hypersensitivity asthma. Hypersensitivity pneumonitis usually appears when exposure ceases. Cobalt is listed by the National Toxicology Program (NTP) as a 2B carcinogen, anticipated to be carcinogenic from studies in experimental animals.

COLUMBIUM (NIOBIUM): Eye or skin irritant, may cause kidney damage.

COPPER: May irritate the upper respiratory tract, may include a metallic or sweet taste. May also cause metal fume fever.

IRON OXIDE: Repeated inhalation of iron oxide fume or dust causes benign pneumoconiosis (siderosis), but generally does not cause symptoms in the exposed person.

MANGANESE: Acute effects include skin and eye irritation and metal fume fever. Chronic exposure may lead to central nervous system symptoms of headaches, changes in motor activity and psychological disturbances.

MOLYBDENUM: Insoluble compounds of molybdenum have a lower order of toxicity. Molybdenum trioxide is an irritant to eyes and mucous membranes.

NICKEL: Known to cause contact dermatitis and is a respiratory tract irritant. Nickel refining and specific compounds are considered respiratory carcinogens to humans. The International Agency for Research on Cancer lists elemental nickel as a 2B, possibly carcinogenic to humans. The National Toxicological Program (NTP) lists nickel as reasonably anticipated to be carcinogenic from studies in experimental animals. The American Conference on Governmental Industrial Hygienists recommends that nickel compound be differentiated according to solubility for their carcinogenic effects.

SELENIUM: Selenium dust vapors and fumes are irritants of the eyes, mucous membranes and skin. Chronic exposure may cause central nervous system effects and gastrointestinal disturbances. Selenium is listed by the Nation Toxicological Program (NTP) as a 2B, anticipated to be carcinogenic from studies in experimental Animals.

COMPANY INFORMATION

COMPANY NAME: ORTHO SPECIALTIES
COMPANY ADDRESS: 3820 OHIO AVE - SUITE 15
 ST. CHARLES, IL 60174
COMPANY PHONE: 630-443-0225
COMPANY FAX: 630-443-0224
COMPANY WEB ADDRESS: www.orthospecialties.com

STAINLESS STEEL – TYPE 302	
DOCUMENT NUMBER:	SDS18
REVISION DATE:	09/26/2014
REVISION:	REV. E
NUMBER OF PAGES:	5

3.) HAZARDOUS IDENTIFICATION SPECIFIC HEALTH EFFECTS (con't):

- TANTALUM:** Considered to have a low order of toxicity. As surgical implant material, it has demonstrated its physiological inertness.
- TITANIUM:** A mild pulmonary irritant generally regarded as nuisance dust.
- TUNGSTEN:** Both tungsten and tungsten carbide pose an extremely low order of toxicity. Tungsten is considered an inert dust
- VANADIUM:** The oxides of vanadium are toxic. May cause irritation to the eyes and respiratory tract. May cause bronchitis with wheezing and chest pain. A sensitizer, with repeated exposure may cause more severe respiratory symptoms.
- ZIRCONIUM:** Considered to have a low order of toxicity. Skin rash has been associated with exposure to deodorant containing zirconium.

4.) FIRST-AID MEASURES

- As shipped, the steel is an article. The likelihood for hazardous consequences through eye or skin contact, inhalation or ingestion would be considered minimal.
- INHALATION:** Remove person from exposure to fresh air. If breathing difficulty occurs, get prompt medical attention.
- SKIN/ EYE CONTACT:** Flush with plenty of water for 15 minutes; seek medical attention if irritation persists. Wash skin with soap and water, if rash develops, seek medical attention.
- INGESTION:** Seek Medical Attention

5.) FIRE FIGHTING MEASURES

- Flash Point and Method: Not Applicable
- Flammability Limits: Not Applicable
- Auto-ignition Temperature: Not Available
- Melting Point: 2400 – 2800 degrees F
- General Hazard: In the form shipped, these specialty metals are not combustible
- Firefighting Instructions: No special instructions for product shipped
- Firefighting Equipment: No special equipment for product as shipped
- Hazardous
- Combustion Products: In the form shipped, hazardous decomposition products are not Expected

6.) ACCIDENTAL RELEASE MEASURES

- Land/Water spill: As shipped, this product does not pose a hazard to the environment.

7.) HANDLING AND STORAGE

- Storage Temperature: Not Applicable
- Storage Pressure: Not Applicable
- General: Store away from acids and oxidizers

COMPANY INFORMATION

COMPANY NAME: ORTHO SPECIALTIES
COMPANY ADDRESS: 3820 OHIO AVE - SUITE 15
 ST. CHARLES, IL 60174
COMPANY PHONE: 630-443-0225
COMPANY FAX: 630-443-0224
COMPANY WEB ADDRESS: www.orthospecialties.com

STAINLESS STEEL – TYPE 302

DOCUMENT NUMBER:	SDS18
REVISION DATE:	09/26/2014
REVISION:	REV. E
NUMBER OF PAGES:	5

8.) EXPOSURE CONTROL / PERSONAL PROTECTION

ENGINEERING CONTROLS:

The use of local exhaust ventilation is recommended to control emissions near the source of metal being cut, ground, welded or melted.

PERSONAL PROTECTION:

When handling the steel product, leather gloves are recommended. Additional personal protective equipment is dependent on the operation performed, for example: safety glasses and a face shield when grinding this product.

If industrial hygiene monitoring reveals an overexposure during the processing of the product, engineering controls are required to be installed to reduce exposures below OSHA permissible exposure limits. In the absence of feasible engineering controls, wear a NIOSH approved respirator for protection for the type of particulate generated.

9.) PHYSICAL & CHEMICAL PROPERTIES

Vapor Pressure:	Not Applicable	Vapor Density:	Not Applicable
Specific Gravity:	7.5 – 8.5	Evaporation Rate:	Not Applicable
Solubility in Water:	Insoluble	Freezing Point:	Not Applicable
PH:	Not Applicable	Odor:	Odorless
Boiling Point:	Not Applicable	Appearance:	Gray in color
Viscosity:	Not Applicable	Physical State:	Solid

10.) STABILITY AND REACTIVITY

GENERAL:

Product is stable and hazardous polymerization will not occur.

INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:

Acids, bases and oxidizers.

HAZARDOUS DECOMPOSITION:

None for product as shipped.

11.) TOXICOLOGICAL INFORMATION:

THIS INFORMATION WAS COVERED SECTION # 3

12.) ECOLOGICAL INFORMATION:

THERE IS NO DATA AVAILABLE

13.) DISPOSAL CONSIDERATIONS:

GENERAL:

Recycling of all metallic byproducts as scrap is strongly encouraged. If byproducts need to be treated And/or disposed of as wastes, hazardous wastes characterizations must be performed prior to treating and \or Disposing. Contact appropriate parties to ensure compliance with all federal, state and local rules and regulations related to waste treatment and disposal.

14.) TRANSPORTATION INFORMATION:

For Hazardous Wastes:	D O T (Department of Transportation)	
Proper Shipping Name:	Hazardous Waste Solid, n.o.s. (Component A, Component B)	
Hazard Class:	9 Identification Number:	NA3077
Packing Group:	III Emergency Response Guide Number:	171

COMPANY INFORMATION

COMPANY NAME: ORTHO SPECIALTIES
COMPANY ADDRESS: 3820 OHIO AVE - SUITE 15
 ST. CHARLES, IL 60174
COMPANY PHONE: 630-443-0225
COMPANY FAX: 630-443-0224
COMPANY WEB ADDRESS: www.orthospecialties.com

STAINLESS STEEL – TYPE 302	
DOCUMENT NUMBER:	SDS18
REVISION DATE:	09/26/2014
REVISION:	REV. E
NUMBER OF PAGES:	3

15.) REGULATORY INFORMATION:

TSCA CERCLA SARA Title III	(Toxic Substances Control Act): (Comprehensive Response & Liability Act): (Superfund Amendments & Reauthorization Act): 311/312 Hazardous Categories	Not Applicable Not Applicable Not Applicable for storage of items as shipped, however if processed, end product may require reporting. Product ingredients subject to reporting requirements may include: chromium, nickel, manganese, cobalt, copper, vanadium, titanium, or aluminum
----------------------------------	---	---

Regulations such as the Clean Air Act, Clean Water Act, Resource Conservation & Recovery Act may apply to the Handling of steel grindings and particulates from processing.

California Safe Drinking Water Act (Prop 65) listing:
 COMPONENT CAS NUMBER
 NICKEL 7440-02-0
 COBALT 7440-48-4

Governors list of chemicals known to cause cancer and reproductive toxicity includes hexavalent compounds of Chromium and nickel dust from pyrometallurgical processing.

16.) OTHER INFORMATION:

HAZARD RATINGS:

NFPA

Health: 0 (as shipped) 2 (if ground), welded or melted
 Flammability: 0
 Reactivity: 0

HMIS

Health: 0 (as shipped) 2 (if ground), welded or melted
 Flammability: 0
 Reactivity: 0

*****The above information is supplied and is specific to the product or products mentioned in this disclosure only. Ortho Specialties, Inc. furnishes this information without warranty of any kind, expressed or implied. By supplying the above information, Ortho Specialties, Inc. assumes no legal responsibility of any kind (including its own negligence) for the use or reliance upon the data supplied as well as the product mentioned in this foreclosure.