

COMPANY INFORMATION

COMPANY NAME: ORTHO SPECIALTIES
COMPANY ADDRESS: 3820 OHIO AVE - SUITE 15
 ST. CHARLES, IL 60174
COMPANY PHONE: 630-443-0225
COMPANY FAX: 630-443-0224
COMPANY WEB ADDRESS: www.orthospecialties.com

**LIGHT BOND FILLED SEALANT
 W/FLUORIDE**

DOCUMENT NUMBER: SDS44
REVISION DATE: 09/26/2014
REVISION: REV. E
NUMBER OF PAGES: 2

1 – IDENTIFICATION OF SUBSTANCE/PREPARATION

PRODUCT NAME: LIGHT BOND FILLED SEALANT W/FLUORIDE

2 – COMPOSITION/INFORMATION ON INGREDIENTS

| Ingredient | Concentration Range (%) | CAS Number | Symbol/Risk Classification | OSHA-PEL (mg/m3) | ACGIH-TLV (mg/m3) | LD50 (mg/kg., rat/oral) |
|----------------------------------|-------------------------|------------|----------------------------|------------------|-------------------|-------------------------|
| Glass filler | >20 | 65997-18-4 | N A | 15 | 10 | N D |
| Hydrofluoride methacrylate | 1-3 | N A | Xi; R36/38-43 | N D | N D | N D |
| Urethane dimethacrylate. | >10 | 74389-53-0 | Xi; R36/38-43 | N D | N D | N D |
| Triethyleneglycol dimethacrylate | >10 | 109-16-0 | Xi; R36/38-43 | N D | N D | N D |

3 – HAZARDS IDENTIFICATION

Irritates the eyes, May irritate the skin. May cause allergic reaction on skin.

4 – FIRST-AID MEASURES

INHALATION: Provide fresh air and rest.
SKIN CONTACT: Wash with soap and water.
EYE CONTACT: Flush with running water for at least 15 minutes while keeping eye lids open; seek medical attention.
INGESTION: Drink two glasses of water or milk. Seek medical attention if a substantial amount has been ingested.

5 – FIRE-FIGHTING MEASURES

FIRE-FIGHTING MEDIA: Dry chemical powder, foam or carbon dioxide.
FIRE AND EXPLOSION RISKS: Upon combustion, irritating gases may form.

6 – ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Prevent skin/eye contact, Provide ventilation.
ENVIRONMENTAL PRECAUTIONS: Avoid ground water contamination.
METHODS FOR CLEANING UP: Wipe with damp paper towel. Discard properly.

7 – HANDLING AND STORAGE

Store in ventilated, dry, cool (less than 22C/ 72 F) place, avoid high light intensity >10000 lux, this product is used exclusively for dental purposes by trained personnel

8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection: Use protective eyewear.
Hand Protection: Use protective gloves.
Respiratory Protection: Avoid prolonged breathing of vapors of uncured material.
Skin Protection: Use any necessary hygiene measures.

COMPANY INFORMATION

COMPANY NAME: ORTHO SPECIALTIES
COMPANY ADDRESS: 3820 OHIO AVE - SUITE 15
 ST. CHARLES, IL 60174
COMPANY PHONE: 630-443-0225
COMPANY FAX: 630-443-0224
COMPANY WEB ADDRESS: www.orthospecialties.com

**LIGHT BOND FILLED SEALANT
 W/FLUORIDE**

| | |
|-------------------------|-------------------|
| DOCUMENT NUMBER: | SDS44 |
| REVISION DATE: | 09/26/2014 |
| REVISION: | REV. E |
| NUMBER OF PAGES: | 2 |

9 – PHYSICAL / CHEMICAL PROPERTIES

| | | | |
|------------------------|-------------------------|---------------------------|-----|
| Appearance: | Viscous Liquid | Vapor Pressure @ 20C/68F: | N/A |
| Color: | Lt. Yellow, Translucent | Miscibility: | N/A |
| Odor: | Methacrylate | Vapor Density: | N/A |
| Solubility (H2O, fat): | Insoluble | pH: | N/A |
| Boiling Point / Range: | N/A | Evaporation Rate: | N/A |
| Melting Point / Range: | N/A | Viscosity: | N/A |
| Flash Point: | >75C/167 F | Partition Coefficient: | N/A |
| Conductivity: | N/A | Auto flammability: | N/A |
| Explosive Properties: | N/A | Flammability: | N/A |
| Oxidizing Properties: | N/A | Relative Density: | >1 |

10 – STABILITY AND REACTIVITY

Avoid high temperatures, and high intensity light (>10000 lux).

11 – TOXICOLOGICAL INFORMATION

Eye Contact: Irritates the eyes.
 Skin Contact: May irritate the skin.
 Sensitization: May cause allergic reaction on contact with the skin.
 Other: N/A.

12 – ECOLOGICAL INFORMATION

N/A

13 – DISPOSAL CONSIDERATIONS

Refer to any Community provisions relating to waste. In their absence, refer to National or Regional provisions relating to waste.

14 – TRANSPORT INFORMATION

No special precautions.

15 – REGULATORY INFORMATION

Classification: Xi Irritant, R36 Irritating to eyes. R38 Irritating to skin. R43 May cause sensitization by skin contact.
 Safety: Refer to any applicable National laws.

16 – OTHER INFORMATION

NOTE: This information is believed to be correct as of the date of this MSDS. The manufacturer makes no representation as to the completeness or accuracy of this information and supplies it on the condition that the person receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will the manufacturer be responsible for damages of any nature whatsoever resulting from the use of or reliance upon the information contained herein.